

**DECLARATION OF PERFORMANCE
No. DUR-13001-PORNAT**

1. Unique identification code of the product type.
Type, batch or serial number or any other element allowing identification of the product.

**DRY-PRESSED CERAMIC TILES,
WITH WATER ABSORPTION $E_b \leq 0.5\% \leq 3\%$**

2. Intended use(s)

For internal walls and floorings

3. Name or registered trade mark and contact address of the manufacturer

**CASA DEPOT Ctra. CV-20 – Av. Mediterraneo, 52
12200 ONDA (CASTELLÓN) - ESPAÑA**

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory if relevant

NPD

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1-A1 _{fl}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 1300 N	
Slipperiness, as:	NPD	
Tactility	NPD	
Bond strength/adhesión, for:		
Cementitious adhesive, type C2	$C2 < 1,0$ N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Onda, February 1st, 2022